

# Gibus Drop Awnings DIM6



## DIM 6 HOUSING.

Fabric with windward. Arm spring projection 62 cm. The rotation of the arms takes place on the pivot fixed inside the lateral guides. The arms can be adjusted on fixed position ranging 180°. After the rotation the arm can go down with the terminal bar at the end of the lateral guides. Winch, normal motor or motor with remote control.




## DIM 6G HOUSING.

With aluminum lateral guides. The guides support the housing.



## DIM 6 ZIP.

The fabric slides inside the side profiles, that have a special way for runner of the zip, welded on the fabric. The runnerway Zip protects the awnings from the wind. The side Zips keep the fabric inside the profile and preserve it from wind and atmospheric agents. With the right fabric it can become shading and blackout and outside installed it can contribute to protect from the atmospheric agents. The awning can be installed only in vertical position. The profiles supports the housing. Winch, normal motor or motor with remote control.



**Gibus**

[www.gibus.it](http://www.gibus.it)

**MOCELLINI srl**  
**Via Vecchia di Cuneo, 85**  
**12011 BORG SAN DALMAZZO (CN)**  
**tel +390171 260184**  
**e-mail: info@mocellini.com**

# Gibus Drop Awnings Tekas


A set of drop awnings inside to an housing with a new system of aluminium heads. Wall and ceiling-mounted installation. Ideal for darkening, windows of medium and big dimensions, and for the protection from atmospheric agents. Winch, normal motor or motor with remote controll. The robustness, the functionality, the technology, and the utilized good materials allow us to grant the 5 years warranty.



**TEKA 0.** Standard fixing hooks for railings and floor anchorage.



**TEKA 1.** Standard adjustable arms for railings anchorage.



**TEKA OG.** Aluminium lateral guides with standard expansion pin. Bar support Omega 50 mm on request.



**TEKA 5.** Aluminium lateral guides with standard expansion pin. Bar support Omega 50 mm on request. Arm spring dimension 62 cm. The arm rotation takes place on the pivot fixed inside the lateral guides. After rotation, the arms can go down with the terminal at the end of the lateral guides.



**TEKA GC.** Stainless cable lateral guides 4 mm with inferior brackets tie-rod.



**Gibus**

[www.gibus.it](http://www.gibus.it)